Laserliner[®]

SuperSquare-Laser 2G Plus



Green laser technology

- Extremely bright green laser lines the DLD technology produces high-quality lines, a clean, clear and therefore easily visible line image.
- The 2 highly visible laser lines are ideally suited to floor alignment.
- Vertical and horizontal levelling on walls
- The applied lay edges and contact surface make it easy to position floor tiles.
- Optimal alignment of areas which are difficult to access
- Clean application on all surfaces
 with pins as well
- Vials to adjust the device
- Can be used as a laser spirit level
- Allows for measurement of sloped planes

TECHNICAL DATA

ANGLE PRECISION ± 0,5 mm / m
OPERATING RANGE (depending on room illumination) 25 m
OPERATING TEMPERATURE 0°C+50°C
STORAGE TEMPERATURE -10°C+70°C
LASER WAVELENGTH 515 nm
LASER CLASS 2 / < 1 mW
POWER SUPPLY 2 x 1,5V AA
OPERATING TIME 10 h
DIMENSIONS (W x H x D) 200 x 48 x 100 mm
WEIGHT incl. batteries 272 g



UMAREX GmbH & Co. KG · Donnerfeld 2 · 59757 Arnsberg · Germany · Tel. +49 2932 638-300 · Fax +49 2932 638-333 · laserliner@umarex.de · www.laserliner.com