Laserliner

CompactCube-Laser 3 Plus

Automatic cross-line laser with lateral 90° laser line, slope function and universal clamping bracket

CompactCube-Laser 3

- PowerBright-Laser: Special high-performance laser diodes project extremely visible laser lines.
- This unit produces 3 very visible laser lines which make it outstanding for the alignment of tiles, wall studding, windows, doors, etc.
- The **2 vertical lines** are aligned at right angles to one another.
- Automatic Level: automatic alignment by virtue of a magnetic pendulum system.
- Individually switchable laser lines
- Additional slope mode to align angled surfaces
- Out-Off-Level: is indicated by optical signals when the unit is outside its self-levelling range.
- Transport lock: A pendelum lock protects unit during transport.
- Small, compact design fits in any toolbox
- Sturdy, ergonomically designed, rubberised casing

FlexClamp Plus

- Easy-to-adjust clamping bracket for optimum use of cross line lasers in interior finishing applications
- Versatile damage free mounting options for surfaces
- Easy-to-adjust height and position of the measuring device
- Suitable for all laser measuring devices with 1/4" threads







Adjustable and free mounting options

ADTICLE	ADTICLE NO	EAN-CODE	DII
ARTICLE	ARTICLE NO	EAN-CODE	PU
CompactCube-Laser 3 Plus	081.340A	4 021563 703548	2

















TECHNICAL DATA

SELF-LEVELLING RANGE ± 3°

ACCURACY ± 0,35 mm/m

LEVELLING automatic

OPERATING RANGE (depending on brightness of area) 15 m

LASER WAVELENGTH 635 nm

LASER CLASS 2 / < 1 mW

POWER SUPPLY 3 x 1.5 V alkaline batteries (type AAA, LR6)

OPERATING TIME


with laser cross at front: approx. 20 hours with all laser lines: approx. 9 hours

OPERATING CONDITION 0°C ... +40°C STORAGE CONDITIONS -10°C ... +70°C

DIMENSIONS (W x H x D)

69 x 69 x 65 mm (CompactCube-Laser 3)

WEIGHT (incl. batteries) 285 g (CompactCube-Laser 3)





CompactCube-Laser 3 Plus

inclusive CompactCube-Laser 3

- + FlexClamp Plus
- + carrying case
- + laser enhancement glasses
- + batteries

Packing dimension (W \times H \times D) 340 x 275 x 123 mm